

Pre-Oiled Timber Decking & Cladding. The Future Of Timber Protection.

Protect your pre-oiled timber


What is 'pre-oiled' timber?

Pre-oiled timber has one coat of oil already applied. To fully protect your pre-oiled timber, apply top coating within 12 weeks of installation.

The pre-oiled advantage:

360° Protection

- Minimised moisture absorption helps timber last longer.
- Reduced likelihood of warping, cupping or splitting.
- On-site coating protects top surface only.



Saves time

- No need to weather timber, simply clean and coat.
- Less prep means less time on-site, helping you finish faster.



Long lasting protection requires a high performance finish

Your pre-oiled timber is protected with **Intergrain® Industrial Uni Timber Oil**. Uni Timber Oil can be overcoated with most oil based or water based finishes.

TIP: During timber installation, touch up any cut-ends with your chosen finish to help maintain 360° protection.

Two steps for lasting protection:

1. **Clean:** ensure surface is clean.

If required, thoroughly scrub with **Intergrain® UltraPrep™ Timber Cleaner**.

2. **Coat:** once dry, apply 2 coats of your chosen oil based or water based finish. Do not apply a mineral oil based finish.



For long term protection:

1. Conduct regular maintenance inspections to ensure your coating is still repelling water and the finish is in sound condition.
2. If maintenance is required, thoroughly scrub with **Intergrain® UltraPrep™ Timber Cleaner** and apply a fresh coat.



Intergrain

For more information on the entire Intergrain range, FREECALL 1800 630 285 or visit intergrain.com.au

© Intergrain and UltraDeck are registered trade marks. ™ UltraPrep is a trademark. Intergrain Timber Finishes, 1956 Dandenong Road, Clayton Victoria 3168. For more information, talk to your Intergrain Account Executive or phone 1800 630 280.

PRE-OIL/05/2020